Verifone

## **RubyCi** ALL-IN-ONE STORE MANAGEMENT SOLUTION

RubyCi is the latest POS solution offering from Verifone. It is equipped with a functional site controller included in one piece of hardware providing fast, efficient, complete store management. The combination of POS and site controller makes this solution the only one of it's kind in the marketplace. Now, site owners have the ability to consolidate as well as upgrade their operating technology at the same time.

RubyCi is equipped with a high capacity processor allowing it to grow in functionality as business needs change or expand. The sleek touch screen hardware allows for more counter space and a smaller footprint for each work station.

## SITE SUPPORT

- Up to 16 fueling positions
- Up to 3 indoor POS workstations

## SPECIFICATIONS

| Processor               | 1.86 GHz Dual Core Atom CPU   |
|-------------------------|---|
| Memory                  | 2GB Solid State SATA Flash, 160GB HDD, scalable to 1+TB<br>2GB DDR3 RAM, scalable to 4GB  |
| Display                 | LED-backlit 15 inch TFT XGA high brightness display<br>Touch Screen, 15 inch infrared touch screen with high transmissivity<br>anti-glare glass   |
| Connectivity            | 10/100/100 BaseT LAN port, 6 USB ports<br>2 Cash Drawer ports with RJ-45 connectors for solenoid control<br>DVI connector for second display, Audio mic-in and line-out<br>connectors, 100/240V 50/60Hz operation                                 |
| Other Standard Features | 3-track MSR for reading loyalty and ID cards  |
| Communications          | 8 RJ-45, RS-232 serial ports with optional software controlled 12 Volt<br>DTR power, Diagnostic Panel for fast debugging; includes soft reset<br>button, diagnotic console port, 7-segment status LEDs, heartbeat<br>LED, and diagnostic switches |
| Safety                  | UL, cUL, CE Mark capability, EMI: FCC Class A (USA) & CISPR 22<br>Class A (EU), ESD: IEC 1000 4-2 (8 KV contact, 4 KV air)  |
| Power                   | Voltage: 5-12V DC, 500mA (maximum)  |
| Environmental           | Temperature: operating range 0-40° C, non-operating range<br>-20 to 60° C - Humidity: operating range 15% to 95%, relative<br>humidity at 40° C   |
| Physical Dimensions     | 16"H x 14 3/4"W x 12"D  |
|                         |   |

©2014 Verifone, Inc. All rights reserved. Verifone, the Verifone logo, are either trademarks or registered trademarks of VeriFone in the United States and/or other countries. All other trademarks or brand names are the properties of their respective holders. All features and specifications are subject to change without notice. Reproduction or posting of this document without prior Verifone approval is prohibited. 11/14 46765 Rev B NO

Acterra Group, Inc. PO Box 160 Marion, IA 52302 TF 800.289.7371 www.acterragroup.com EMV READY HARDWARE

> Speed Through Lines with the Fastest Processor in the Industry



Manage Operations Quicker and Easier with Cloud Management Tools



